

Pacific Gas and Electric Company
Energy-Efficiency Rebates for Your Business

Restaurant Catalog

Saving energy for a brighter future



Together, Building
a Better California

Table of Contents

Commercial Cooking

Commercial Combination Ovens/Steamers (Electric)	1
Commercial Combination Ovens/Steamers (Natural Gas)	2
Commercial Conveyor Broilers	3
Commercial Convection Ovens (Electric)	4
Commercial Convection Ovens (Natural Gas)	4
Commercial Conveyor Ovens (Natural Gas)	5
Commercial Rack Ovens (Natural Gas)	5
Commercial Fryers (Electric)	6
Commercial Fryers (Natural Gas)	7
Commercial Griddles (Electric)	8
Commercial Griddles (Natural Gas)	8
Commercial Steam Cookers (Electric)	9
Commercial Steam Cookers (Natural Gas)	9

Commercial Dishwashing

Low Flow Pre-Rinse Spray Valves	10
Single Tank Door-Type Commercial Dishwasher	10

Wrapping

On-Demand Hand Wrap Machine	11
---------------------------------------	----

Holding

Insulated Holding Cabinets	11
--------------------------------------	----

Commercial Cooling

Commercial Glass Door Refrigerators	12
Commercial Solid Door Refrigerators	13
Commercial Solid Door Freezers	14
Commercial Ice Machines	15

Commercial Ventilation

Demand Control Kitchen Ventilation	16
--	----

Lighting

LED Troffers and Integrated Troffer Retrofit Kits	17
LED Outdoor Area Lighting	20
LED Accent, Surface, Pendant, Track and Recessed Downlight Fixtures	22

Refrigeration

Efficient Evaporator Fan Motors	23
Auto-Closers for Walk-in Cooler or Freezer Doors	24
Evaporator Fan Controllers for Walk-in Coolers and Freezers	24

Insulation

Pipe Insulation	25
-----------------------	----

Commercial Cooking

Commercial Combination Ovens/Steamers (Electric)

Requirements:

- Oven must have a cooking energy efficiency of 50 percent or greater in steam mode and 70 percent cooking energy efficiency or greater in convection mode, utilizing American Society for Testing and Materials (ASTM) Standard F2861.
- Oven must meet the idle energy rate requirements in the accompanying *Electric Combination Ovens/Steamers Rebates* table, utilizing ASTM Standard F2861.
- Installation address must have a commercial electric account with PG&E.
- For a list of rebate-qualified commercial combination ovens/steamers, visit caenergywise.com/rebates.

Exclusions:

- 2/3-size combination ovens are not eligible.
- Electric combination ovens with a pan capacity of < 5 are not eligible.

Additional details:

For more information about food service, visit PG&E Food Service Technology Center at fishnick.com.

Electric Combination Ovens/Steamers Rebates

Pan Capacity	Steam Mode/Idle Energy Rate	Convection Mode/Idle Energy Rate
Less than 15 pans*	5.0 kW or less	2.0 kW or less
15–28 pans*	6.0 kW or less	2.5 kW or less
More than 28 pans*	9.0 kW or less	4.0 kW or less

*Combination oven/steamer pan capacity is based on the maximum capacity of full-size, 2½-inch deep hotel pans. This must be consistent with the number of pans used to meet the energy-efficiency qualifications for ASTM F2861.

Rebate Code	Description	Rebate/Unit Measure
HA16	Commercial Combination Oven/Steamer Electric (< 15 pans)	\$1,000/unit
F100	Commercial Combination Oven/Steamer Electric (15–28 pans)	\$1,000/unit
HA19	Commercial Combination Oven/Steamer Electric (> 28 pans)	\$4,000/unit

For more information and for the most up-to-date catalogs, visit pge.com/businessrebates, or call our Business Customer Service Center at 1-800-468-4743.

Commercial Combination Ovens/Steamers (Natural Gas)

Requirements:

- Oven must have a cooking energy efficiency of 38 percent or greater in steam mode and 44 percent or greater in convection mode, utilizing American Society for Testing and Materials (ASTM) Standard F2861.
- Oven must meet the idle energy rate requirements in the accompanying *Gas Combination Ovens/Steamers Rebates* table, utilizing ASTM Standard F2861.
- Installation address must have a commercial natural gas account with PG&E.
- For a list of rebate-qualified commercial combination ovens/steamers, visit caenergywise.com/rebates.

Exclusions:

- 2/3-size combination ovens are not eligible.
- Gas combination ovens with a pan capacity < 6 are not eligible.

Gas Combination Ovens/Steamers Rebates

Pan Capacity	Steam Mode/Idle Energy Rate	Convection Mode/Idle Energy Rate
Less than 15 pans*	15,000 Btuh or less	8,000 Btuh or less
15–28 pans*	18,000 Btuh or less	10,000 Btuh or less
More than 28 pans*	28,000 Btuh or less	16,000 Btuh or less

*Combination oven/steamer pan capacity is based on the maximum capacity of full-size, 2½-inch deep hotel pans. This must be consistent with the number of pans used to meet the energy-efficiency qualifications for ASTM F2861.

Rebate Code	Description	Rebate/Unit Measure
HA48	Commercial Combination Oven/Steamer Natural Gas (< 15 pans)	\$700/unit
F101	Commercial Combination Oven/Steamer Natural Gas (15–28 pans)	\$1,000/unit
HA49	Commercial Combination Oven/Steamer Natural Gas (> 28 pans)	\$2,000/unit

Commercial Conveyor Broilers

Requirements:

- Conveyor broiler must have a catalyst and a maximum input rate less than 80 kBtu/h or a dual stage or modulating gas valve with a capability of throttling the input rate below 80 kBtu/h.
- Conveyor broiler must be installed under a Type I hood.
- Installation address must have a commercial natural gas account with PG&E.
- For a list of rebate-qualified commercial conveyor broilers, visit caenergywise.com/rebates.

Exclusions:

Underfired broilers, char broilers, steakhouse or overfired broilers, solid fuel broilers, and salamanders are not eligible.

Additional details:

- Width is listed for cooking cavity.
- Broilers may have multiple parallel conveyors in a single cavity.
- Batch conveyor broilers are eligible.

Rebate Code	Description	Rebate/Unit Measure
FS023	Energy Efficient Commercial Conveyor Broilers < 22 inch wide conveyor	\$2,000/unit
FS024	Energy Efficient Commercial Conveyor Broilers 22–28 inch wide conveyor	\$2,500/unit
FS025	Energy Efficient Commercial Conveyor Broilers > 28 inch wide conveyor	\$3,000/unit

Commercial Convection Ovens (Electric)

Requirements:

- Qualifying models must be listed in the California Energy Commission's (CEC) database.
- Model must meet ENERGY STAR® Version 2.2 specification or have a tested heavy-load (potato) cooking energy efficiency of 71 percent or more, utilizing American Society for Testing and Materials (ASTM) Standard F1496.
- Full-size electric ovens (less than or equal to 5 pans) must have an idle rate of 1.6 kilowatts (kW) or less.
- Large full-size ovens (greater than 5 pans) must have an idle rate of 1.9 kW or less and a heavy-load cooking energy efficiency of 73 percent or more.
- Half-size electric ovens must have an idle rate of 1.0 kW or less.
- Installation address must have a commercial electric account with PG&E.
- For a list of rebate-qualified commercial convection ovens, visit caenergywise.com/rebates.

Rebate Code	Description	Rebate/Unit Measure
F187	Commercial Convection Oven Electric	\$350/oven

Commercial Convection Ovens (Natural Gas)

Requirements:

- Qualifying models must be listed in the CEC database.
- Model must meet ENERGY STAR Version 2.2 specification or have a tested heavy-load (potato) cooking energy efficiency of 46 percent or more, utilizing ASTM Standard F1496.
- Full-size gas ovens (less than or equal to 5 pans) must have an idle rate of 12,000 Btuh or less.
- Large full-size ovens (greater than 5 pans) must have an idle rate of 13,000 Btuh or less.
- Installation address must have a commercial natural gas account with PG&E.
- For a list of rebate-qualified commercial convection ovens, visit caenergywise.com/rebates.

Rebate Code	Description	Rebate/Unit Measure
F188	Commercial Convection Oven Natural Gas	\$500/oven

Commercial Conveyor Ovens (Natural Gas)

Requirements:

- Oven must have a tested baking energy efficiency of 42 percent or greater and must have a tested idle energy rate that is 57,000 Btuh or less, utilizing American Society for Testing and Materials (ASTM) Standard F1817.
- Installation address must have a commercial natural gas account with PG&E.
- For a list of rebate-qualified commercial conveyor ovens, visit caenergywise.com/rebates.

Additional details:

Multiple-deck oven configurations are paid per qualifying oven deck.

Rebate Code	Description	Rebate/Unit Measure
F208	Commercial Conveyor Oven Natural Gas	\$500/oven deck

Commercial Rack Ovens (Natural Gas)

Requirements:

- Both single and double full-size rack ovens are eligible.
- Oven must have a tested baking energy efficiency of 50 percent or greater, utilizing ASTM Standard F2093.
- Installation address must have a commercial natural gas account with PG&E.
- For a list of rebate-qualified commercial rack ovens, visit caenergywise.com/rebates.

Exclusions:

Mini rack ovens (less than 15 pans) are not eligible.

Rebate Code	Description	Rebate/Unit Measure
F207	Commercial Rack Oven Natural Gas	\$2,000/oven



Commercial Fryers (Electric)

Requirements:

- Electric fryer (vat width less than 18 inches) must meet ENERGY STAR® Version 2.0 specification for energy efficiency or must have a tested heavy-load cooking energy efficiency of 80 percent and an idle energy rate less than or equal to 1,000 watts (W), utilizing American Society for Testing and Materials (ASTM) Standard F1361.
- Electric large vat fryer (vat width greater than or equal to 18 inches) must meet ENERGY STAR Version 2.0 specification for energy efficiency or must have a tested heavy-load cooking energy efficiency of 80 percent and an idle energy rate less than or equal to 1,100 W, utilizing ASTM Standard F2144.
- Installation address must have a commercial electric account with PG&E.
- For a list of rebate-qualified commercial fryers, visit caenergywise.com/rebates.

Additional details:

Multiple vat configurations are paid per qualifying vat.

Rebate Code	Description	Rebate/Unit Measure
F205	Commercial Fryer Electric	\$650/vat



Commercial Fryers (Natural Gas)

Requirements:

- Gas fryer (vat width less than 18 inches) must meet ENERGY STAR® Version 3.0 specification for energy efficiency or must have a tested heavy-load cooking energy efficiency of 50 percent and an idle energy rate less than or equal to 9,000 Btuh, utilizing American Society for Testing and Materials (ASTM) Standard F1361.
- Gas large vat fryer (vat width greater than or equal to 18 inches) must meet ENERGY STAR Version 3.0 specification for energy efficiency or must have a tested heavy-load cooking energy efficiency of 50 percent and an idle energy rate less than or equal to 12,000 Btuh, utilizing ASTM Standard F2144.
- Installation address must have a commercial natural gas account with PG&E.
- For a list of rebate-qualified commercial fryers, visit caenergywise.com/rebates.

Additional details:

Multiple vat configurations are paid per qualifying vat.

Rebate Code	Description	Rebate/Unit Measure
F206	Commercial Fryer Natural Gas	\$749/vat

Commercial Griddles (Electric)

Requirements:

- Griddle must have a tested heavy-load cooking energy efficiency of 70 percent or greater and an idle energy rate of 355 watts (W) per square foot of cooking surface or less, utilizing American Society for Testing and Materials (ASTM) Standard F1275.
- Installation address must have a commercial electric account with PG&E.
- For a list of rebate-qualified commercial griddles, visit caenergywise.com/rebates.

Rebate Code	Description	Rebate/Unit Measure
FS002	Commercial Griddle Electric	\$150/linear ft.

Commercial Griddles (Natural Gas)

Requirements:

- Gas griddle must meet ENERGY STAR® Version 1.2 specification for energy efficiency or must have a tested heavy-load cooking energy efficiency of 38 percent or greater and an idle energy rate of 2,650 Btuh per square foot of cooking surface or less, utilizing ASTM Standard F1275.
- Installation address must have a commercial natural gas account with PG&E.
- For a list of rebate-qualified commercial griddles, visit caenergywise.com/rebates.

Rebate Code	Description	Rebate/Unit Measure
FS003	Commercial Griddle Natural Gas	\$100/linear ft.

Commercial Steam Cookers (Electric)

Requirements:

- Cooker must meet ENERGY STAR® Version 1.2 specification for energy efficiency or must have a tested heavy-load (potato) cooking energy efficiency of 50 percent or greater, utilizing American Society for Testing and Materials (ASTM) Standard F1484.
- Installation address must have a commercial electric account with PG&E.
- For a list of rebate-qualified commercial steam cookers, visit caenergywise.com/rebates.

Rebate Code	Description	Rebate/Unit Measure
F108	Commercial Steam Cooker Electric	\$1,250/steamer compartment

Commercial Steam Cookers (Natural Gas)

Requirements:

- Cooker must meet ENERGY STAR Version 1.2 specification for energy efficiency or must have a tested heavy-load (potato) cooking energy efficiency of 38 percent or greater, utilizing ASTM Standard F1484.
- Installation address must have a commercial natural gas account with PG&E.
- For a list of rebate-qualified commercial steam cookers, visit caenergywise.com/rebates.

Rebate Code	Description	Rebate/Unit Measure
F109	Commercial Steam Cooker Natural Gas	\$2,000/steamer compartment

Commercial Dishwashing

Low Flow Pre-Rinse Spray Valves

Requirements:

- Qualifying models must be listed in the California Energy Commission (CEC) database.
- Pre-rinse spray valves must meet WaterSense specifications and have a tested flow rate of 1.15 gallons per minute (GPM) or less, utilizing American Society for Testing and Materials (ASTM) F2324.
- Installation address must have a commercial natural gas account with PG&E.
- For a list of rebate-qualified low flow pre-rinse spray valves, visit caenergywise.com/rebates.

Rebate Code	Description	Rebate/Unit Measure
FS001	Low Flow Pre-Rinse Spray Valve Natural Gas	\$35/valve

Single Tank Door-Type Commercial Dishwashers

Requirements:

- Qualifying models must meet ENERGY STAR® Version 2.0 plus 15 percent water consumption or have a tested water consumption of less than or equal to 0.75 gallons/rack and idle energy rate less than or equal to 0.70 kilowatts (kW) per the ENERGY STAR test method.
- Qualifying models must be door-type, high temperature sanitizing.
- Installation address must have a commercial electric account with PG&E.
- For a list of rebate-qualified commercial dishwashers, visit caenergywise.com/rebates.

Exclusions:

Low-temperature, dump and fill/tankless, undercounter and conveyor dishwashers are not eligible.

Rebate Code	Description	Rebate/Unit Measure
FS005	Single Tank Door-Type Commercial Dishwasher	\$600/unit

Wrapping

On-Demand Hand Wrap Machines

Requirements:

- Qualifying models must use either a mechanical or optical control system.
- Installation address must have a commercial electric account with PG&E.
- For a list of rebate-qualified on-demand hand wrap machines, visit caenergywise.com/rebates.

Rebate Code	Description	Rebate/Unit Measure
FS009	On-Demand Hand Wrap Machine	\$125/unit

Holding

Insulated Holding Cabinets

Requirements:

- Qualifying models must be listed in the California Energy Commission (CEC) database.
- Cabinet must meet the Consortium for Energy Efficiency (CEE)-Tier 2 specification and must have a tested idle energy rate less than or equal to 20 watts (W) per cubic foot utilizing American Society for Testing and Materials (ASTM) Standard F2140.
- Cabinet (including electric hot-food holding cabinet) must be fully insulated with solid doors.
- Installation address must have a commercial electric account with PG&E.
- For a list of rebate-qualified insulated holding cabinets, visit caenergywise.com/rebates.

Exclusions:

Cook and hold equipment do not qualify.

Rebate Code	Description	Rebate/Unit Measure
F110	Insulated Holding Cabinet Full Size	\$750/unit
F111	Insulated Holding Cabinet Half Size	\$200/unit



Commercial Cooling

Commercial Glass Door Refrigerators

Requirements:

- Qualifying models must be listed in the California Energy Commission (CEC) database.
- Refrigeration system must be built in (packaged).
- Model must meet ENERGY STAR® Version 4.0 specification.
- Installation address must have a commercial electric account with PG&E.
- For a list of rebate-qualified commercial glass door refrigerators, visit caenergywise.com/rebates.

Exclusions:

Units with remote refrigeration systems do not qualify.

Rebate Code	Description	Rebate/Unit Measure
F171	Commercial Glass Door Refrigerator Internal volume less than 15 ft ³	\$40/unit
F172	Commercial Glass Door Refrigerator Internal volume 15 ft ³ –29.9 ft ³	\$60/unit
F173	Commercial Glass Door Refrigerator Internal volume 30 ft ³ –49.9 ft ³	\$80/unit
F174	Commercial Glass Door Refrigerator Internal volume 50 ft ³ or greater	\$100/unit

ft³ equals cubic feet



Commercial Solid Door Refrigerators

Requirements:

- Qualifying models must be listed in the California Energy Commission (CEC) database.
- Refrigeration system must be built in (packaged).
- Model must meet ENERGY STAR® Version 4.0 specification.
- Installation address must have a commercial electric account with PG&E.
- For a list of rebate-qualified commercial solid door refrigerators, visit caenergywise.com/rebates.

Exclusions:

Units with remote refrigeration systems do not qualify.

Rebate Code	Description	Rebate/Unit Measure
F183	Commercial Solid Door Refrigerator Internal volume less than 15 ft ³	\$45/unit
F184	Commercial Solid Door Refrigerator Internal volume 15 ft ³ –29.9 ft ³	\$60/unit
F185	Commercial Solid Door Refrigerator Internal volume 30 ft ³ –49.9 ft ³	\$85/unit
F186	Commercial Solid Door Refrigerator Internal volume 50 ft ³ or greater	\$120/unit

ft³ equals cubic feet



Commercial Solid Door Freezers

Requirements:

- Qualifying models must be listed in the California Energy Commission (CEC) database.
- Refrigeration system must be built in (packaged).
- Model must meet ENERGY STAR® Version 4.0 specification.
- Installation address must have a commercial electric account with PG&E.
- For a list of rebate-qualified commercial solid door freezers, visit caenergywise.com/rebates.

Exclusions:

Units with remote refrigeration systems do not qualify.

Rebate Code	Description	Rebate/Unit Measure
F179	Commercial Solid Door Freezer Internal volume less than 15 ft ³	\$75/unit
F180	Commercial Solid Door Freezer Internal volume 15 ft ³ –29.9 ft ³	\$100/unit
F181	Commercial Solid Door Freezer Internal volume 30 ft ³ –49.9 ft ³	\$160/unit
F182	Commercial Solid Door Freezer Internal volume 50 ft ³ or greater	\$350/unit

ft³ equals cubic feet

Commercial Ice Machines

Requirements:

- Qualifying models must be listed in the California Energy Commission (CEC) database.
- Models must meet ENERGY STAR® Version 3.0 specification.
- Models include machines generating ice cubes that are 60 grams (2 oz.) or lighter. It also includes ice makers that flake, crush and fragment ice cubes.
- Rebate amount depends on ice making rate (pounds per day) and equipment type: self-contained units (SCU), Ice-making heads (IMH) and remote condensing units (RCU).
- Only air-cooled machines qualify for this rebate.
- Customer must purchase the entire Air Conditioning, Heating and Refrigeration Institute (AHRI)-tested ice-making system.
- Remote machines must be purchased with qualifying remote condenser or remote condenser/compressor unit.
- Ice machines must be tested in accordance with the AHRI Standard 810. Visit ahrinet.org to learn more about product information and testing procedures.
- Installation address must have a commercial electric account with PG&E.
- For a list of rebate-qualified commercial ice machines, visit caenergywise.com/rebates.

Rebate Code	Description	Rebate/Unit Measure
FS014	Commercial Ice Machine SCU < 110 lbs/day	\$50/unit
FS015	Commercial Ice Machine SCU 110–200 lbs/day	\$75/unit
FS016	Commercial Ice Machine SCU > 200 lbs/day	\$100/unit
FS017	Commercial Ice Machine IMH < 300 lbs/day	\$75/unit
FS018	Commercial Ice Machine IMH 300–800 lbs/day	\$125/unit
FS019	Commercial Ice Machine IMH 801–1,500 lbs/day	\$200/unit
FS020	Commercial Ice Machine IMH >1,500 lbs/day	\$300/unit
FS021	Commercial Ice Machine RCU < 988 lbs/day	\$200/unit
FS022	Commercial Ice Machine RCU ≥ 988 lbs/day	\$300/unit



Commercial Ventilation

Demand Control Kitchen Ventilation

Demand Control Kitchen Ventilation (DCKV) provides automated continuous control over fan speed in response to temperature, optical or infrared sensors that monitor cooking activity or direct communication with cooking appliances. The ENERGY STAR® Emerging Technology Award has identified DCKV as an innovative technology. To learn more, visit energystar.gov/emergingtech.

Requirements:

- New commercial kitchen exhaust hood control system must be installed in a new or an existing, dedicated commercial kitchen exhaust hood and make-up air system.
- Control system must be used in conjunction with variable-speed fan motor controls.
- Installation address must have a commercial electric account with PG&E.
- For a list of rebate-qualified demand control kitchen ventilation systems, visit caenergywise.com/rebates.

Rebate Code	Description	Rebate/Unit Measure
F150	Demand Control Kitchen Ventilation Electric	\$500/exhaust fan hp*

*horsepower (hp)



Lighting

LED Troffers and Integrated Troffer Retrofit Kits

Requirements:

- Applications received must include products in the below qualifying categories and must be listed as DesignLights Consortium (DLC)-premium classification to qualify for this rebate.
- Only LED troffer fixtures or integrated troffer retrofit kits on the list of prequalified LED fixtures, available at pge.com/ledqpl, in the following DLC product categories, qualify for this rebate:
 - Troffer, 2x2 Luminaires for Ambient Lighting of Interior Commercial Spaces (indoor luminaires)
 - Troffer, 1x4 Luminaires for Ambient Lighting of Interior Commercial Spaces (indoor luminaires)
 - Troffer, 2x4 Luminaires for Ambient Lighting of Interior Commercial Spaces (indoor luminaires)
 - Troffer, 2x2 Luminaires for Integrated Retrofit Kits (indoor retrofit kit)
 - Troffer, 1x4 Luminaires for Integrated Retrofit Kits (indoor retrofit kit)
 - Troffer, 2x4 Luminaires for Integrated Retrofit Kits (indoor retrofit kit)
- DLC-listed initial light output must be greater than or equal to 2,200 lumens (lm) and less than or equal to 6,500 lm to qualify for this rebate.

continued

Exclusions:

- Other fixture configurations, including LED troffer linear retrofit kits, linear ambient luminaires (direct/indirect) or external driver lamp-style retrofit kits (Underwriters Laboratories, Type C), do not qualify for this rebate. These configurations will be considered under the Customized Retrofit Program.
- Exterior or high/low-bay installations of these products do not qualify for this rebate.
- Products in the above listed categories—less than 2,200 lm or greater than 6,500 lm—do not qualify for this rebate and will be considered under the Customized Retrofit Program.

Additional details:

- Customer selects the measure code based on the efficacy in lumens per watt (LPW) of the replacement fixture.
- LED Troffer and Integrated Troffer Retrofit rebates are offered on a per kilolumen (KLM)—1,000 lumens—basis, rather than a per fixture basis. The rebate increases as the efficacy (LPW) of the fixture or kit increases.
- Efficacy is defined by LPW, or how much light is produced by one watt of energy consumed.
- A lumen is the unit of light output: kilolumen = 1,000 lumens.

How to calculate a rebate:

Use the rebate calculator available at pge.com/ledqpl to help determine your total rebate amount.

1. Search for your product using model number, product manufacturer and/or product brand. Alternatively, use the filters for rebate category, product category and/or product metrics to narrow down results and see many options.
2. Once the desired product is found, click on the measure code in the Rebate Information box to be taken to the Rebate Calculator.
3. Enter in the total number of fixtures of a given product that you wish to purchase, and the calculator will calculate the total rebate amount. Enter product and rebate information into the rebate application, as shown.

continued

2x4 LED New Luminaire for Ambient Interior Commercial Spaces

Rebate Code	Description	Rebate/Unit Measure
LT148	≥ 125 LPW and < 140 LPW	\$5/kilolumen (max \$22.50/fixture)
LT149	≥ 140 LPW	\$6/kilolumen (max \$27/fixture)

2x2 LED New Luminaire for Ambient Interior Commercial Spaces

Rebate Code	Description	Rebate/Unit Measure
LT150	≥ 125 LPW and < 140 LPW	\$4.25/kilolumen (max \$19.13/fixture)
LT151	≥ 140 LPW	\$6/kilolumen (max \$27/fixture)

1x4 LED New Luminaire for Ambient Interior Commercial Spaces

Rebate Code	Description	Rebate/Unit Measure
LT152	≥ 125 LPW and < 140 LPW	\$5/kilolumen (max \$22.50 /fixture)
LT153	≥ 140 LPW	\$6/kilolumen (max \$27/fixture)

2x4 LED Integrated Retrofit Kit for Ambient Interior Commercial Spaces

Rebate Code	Description	Rebate/Unit Measure
LT154	≥ 125 LPW and < 140 LPW	\$5/kilolumen (max \$22.50/fixture)
LT155	≥ 140 LPW	\$6/kilolumen (max \$27/fixture)

2x2 LED Integrated Retrofit Kit for Ambient Interior Commercial Spaces

Rebate Code	Description	Rebate/Unit Measure
LT156	≥ 125 LPW and < 140 LPW	\$4.25/kilolumen (max \$19.13/fixture)
LT157	≥ 140 LPW	\$6/kilolumen (max \$27/fixture)

1x4 LED Integrated Retrofit Kit for Ambient Interior Commercial Spaces

Rebate Code	Description	Rebate/Unit Measure
LT158	≥ 125 LPW and < 140 LPW	\$5/kilolumen (max \$22.50/fixture)
LT159	≥ 140 LPW	\$6/kilolumen (max \$27/fixture)

All LED Troffer and Integrated Troffer Retrofit Kit rebates are capped at 4.5 kilolumens per fixture





LED Outdoor Area Lighting

Requirements:

- Applications received must include products in the below qualifying categories and must be listed as DesignLights Consortium (DLC)-premium classification to qualify for this rebate.
- Only LED fixtures or retrofit kits on the list of prequalified LED fixtures available at pge.com/ledqpl, in the following DLC product categories, qualify for this rebate:
 - Outdoor Pole/Arm-mounted Area and Roadway Luminaires (fixtures and retrofit kits)
 - Large Outdoor Pole/Arm-mounted Area and Roadway Luminaires (retrofit kits)
 - Outdoor Pole/Arm-mounted Decorative Luminaires (fixtures and retrofit kits)
 - Parking Garage Luminaires (fixtures and retrofit kits)
 - Outdoor Non/Semi/Full-cutoff Wall-mounted Area Luminaires (fixtures)
 - Outdoor Full-cutoff Wall-mounted Area Luminaires (retrofit kits)
 - Fuel Pump Canopy Luminaires (fixtures and retrofit kits)

Exclusions:

- Self-ballasted, screw-based or pin-based lamps do not qualify.
- Architectural Flood and Spot Luminaires, Landscape/Accent Flood and Spot Luminaires, and Bollards do not qualify.
- Street lighting applications for Pole/Arm-mounted Area and Roadway luminaires do not qualify for these rebates. Please check with PG&E's Government and Community Partnership team for LED street light rebates.
- Interior installations do not qualify for this rebate.

continued

LED Outdoor Pole/Arm-mounted Area, Roadway and Decorative Lighting

Rebate Code	Description	Rebate/Unit Measure
LT304	Install > 390–571 watt LED fixture	\$70/fixture
LT303	Install > 235–390 watt LED fixture	\$65/fixture
LT302	Install > 146–235 watt LED fixture	\$60/fixture
LT301	Install > 107–146 watt LED fixture	\$55/fixture
LT300	Install > 90–107 watt LED fixture	\$45/fixture
LT299	Install > 68–90 watt LED fixture	\$40/fixture
LT298	Install > 45–68 watt LED fixture	\$35/fixture
LT297	Install > 29–45 watt LED fixture	\$30/fixture
LT296	Install 0–29 watt LED fixture	\$25/fixture

LED Outdoor Parking Garage Lighting

Rebate Code	Description	Rebate/Unit Measure
LT308	Install > 88–113 watt LED fixture	\$30/fixture
LT307	Install > 56–88 watt LED fixture	\$25/fixture
LT306	Install > 38–56 watt LED fixture	\$20/fixture
LT305	Install 0–38 watt LED fixture	\$15/fixture

LED Outdoor Wall-mounted Area Lighting

Rebate Code	Description	Rebate/Unit Measure
LT317	Install > 337–493 watt LED fixture	\$105/fixture
LT316	Install > 203–337 watt LED fixture	\$90/fixture
LT315	Install > 126–203 watt LED fixture	\$70/fixture
LT314	Install > 97–126 watt LED fixture	\$60/fixture
LT313	Install > 78–97 watt LED fixture	\$45/fixture
LT312	Install > 58–78 watt LED fixture	\$40/fixture
LT311	Install > 39–58 watt LED fixture	\$35/fixture
LT310	Install > 25–39 watt LED fixture	\$30/fixture
LT309	Install 0–25 watt LED fixture	\$25/fixture

LED Outdoor Fuel Pump Canopy Lighting

Rebate Code	Description	Rebate/Unit Measure
LT324	Install > 99–153 watt LED fixture	\$45/fixture
LT323	Install > 73–99 watt LED fixture	\$40/fixture
LT322	Install > 59–73 watt LED fixture	\$35/fixture
LT321	Install > 46–59 watt LED fixture	\$30/fixture
LT320	Install > 29–46 watt LED fixture	\$25/fixture
LT319	Install > 19–29 watt LED fixture	\$20/fixture
LT318	Install 0–19 watt LED fixture	\$15/fixture

LED Accent, Surface, Pendant, Track and Recessed Downlight Fixtures

Requirements:

- Only fully integrated LED fixtures or retrofit kits on the list of prequalified LED fixtures, available at pge.com/ledqpl, in the following categories, qualify for this rebate:
 - Track or Mono-Point Directional Luminaires, DesignLights Consortium (DLC)
 - Downlights: Recessed, Surface, Pendant or Retrofits (ENERGY STAR®)
 - Accent Light (ENERGY STAR)
 - Wall Sconce (ENERGY STAR)
- LEDs must meet a minimum luminaire efficacy of 35 lumens per watt (LPW).
- Customers are responsible for verifying that new fixtures work with existing lighting controls.
- Downlights intended for installation in insulated ceilings must meet California Energy Commission (CEC) Title 20 requirements.

Exclusions:

Screw-in or pin-based LED lamps are not eligible for these rebates. Visit a participating distributor to receive instant rebates on screw-in LED replacement lamps.

LED Accent and Directional Lighting Fixtures

Rebate Code	Description	Rebate/Unit Measure
LD146	≥ 25 watt LED fixture	\$15.50/fixture
LD145	24 to < 25 watt LED fixture	\$15.50/fixture
LD144	23 to < 24 watt LED fixture	\$15.50/fixture
LD143	22 to < 23 watt LED fixture	\$15.50/fixture
LD142	21 to < 22 watt LED fixture	\$15.50/fixture
LD141	20 to < 21 watt LED fixture	\$15.50/fixture
LD140	19 to < 20 watt LED fixture	\$15.50/fixture
LD139	18 to < 19 watt LED fixture	\$15.50/fixture
LD138	17 to < 18 watt LED fixture	\$13/fixture
LD137	16 to < 17 watt LED fixture	\$13/fixture
LD136	15 to < 16 watt LED fixture	\$13/fixture
LD135	14 to < 15 watt LED fixture	\$13/fixture
LD134	13 to < 14 watt LED fixture	\$13/fixture
LD133	12 to < 13 watt LED fixture	\$13/fixture
LD132	11 to < 12 watt LED fixture	\$11/fixture
LD131	10 to < 11 watt LED fixture	\$11/fixture
LD130	9 to < 10 watt LED fixture	\$11/fixture
LD129	8 to < 9 watt LED fixture	\$8/fixture
LD128	7 to < 8 watt LED fixture	\$8/fixture
LD127	< 7 watt LED fixture	\$8/fixture



Refrigeration

Efficient Evaporator Fan Motors

Requirements:

- Electronically commutated motors (ECM) must be installed in refrigerated display cases, walk-in coolers and freezers.
- Fan motor must replace standard efficiency shaded-pole or permanent split capacitor evaporator fan motor.
- Installation address must have a commercial electric account with PG&E.

Exclusions:

- Motors in walk-ins built after 2008 are not eligible.
- Motors in display cases built after 2011 are not eligible.
- May not be used in conjunction with PG&E rebates for new display cases.

Rebate Code	Description	Rebate/Unit Measure
R145	Efficient ECM Evaporator Fan Motor Medium-Temperature Display Case	\$35/motor
R176	Efficient ECM Evaporator Fan Motor Low-Temperature Display Case	\$50/motor
RF004	Efficient ECM Evaporator Fan Motor Walk-in Cooler	\$75/motor
RF005	Efficient ECM Evaporator Fan Motor Walk-in Freezer	\$75/motor

Auto-Closers for Walk-in Cooler or Freezer Doors

Requirements:

- Auto-closer must be applied to the main insulated door of a walk-in cooler or freezer; additional interior doors are not eligible.
- Auto-closer must be able to firmly close the door when it is within one inch of full closure.
- Installation address must have a commercial electric account with PG&E.

Exclusions:

- Additional interior doors are not eligible.
- Door closers for walk-in coolers or freezers built after 2008 are not eligible.
- Doors that have previously had an auto-closer installed.

Rebate Code	Description	Rebate/Unit Measure
R79	Auto-Closers for Walk-in Cooler Doors	\$75/closer
R80	Auto-Closers for Walk-in Freezer Doors	\$75/closer

Evaporator Fan Controllers for Walk-in Coolers and Freezers

Requirements:

- Existing evaporator fan must run continuously at full speed, with the exception of defrost cycles.
- Evaporator fan must be at least 1/20 horsepower.
- Evaporator fan motor must be single phase.
- Control type must be cycling control (not variable frequency drive).
- Control must reduce fan power at least 75 percent when the compressor cycles off.
- Evaporator must use off-cycle or time-off defrost.
- Installation address must have a commercial electric account with PG&E.

Rebate Code	Description	Rebate/Unit Measure
R53	Evaporator Fan Controllers for Walk-in Coolers and Freezers	\$75/controller

Insulation

Pipe Insulation

Requirements:

- Minimum-qualifying pipe diameter is 0.5 inch.
- Pipe must transfer fluid directly from gas-fired equipment, and insulation materials/accessories must be installed according to manufacturer's instructions.
- Application must include the manufacturer's name, insulation material type and material K-value rating.
 - Acceptable types of insulation for hot water pipes include: elastomeric foam rubber, polyethylene foam, UV-resistant polyethylene foam and rigid polyurethane foam.
 - Acceptable types of insulation for steam pipes include silicone foam rubber, melamine foam, rigid urethane-based foam, cellular glass, rigid fiberglass and rigid mineral wool.

Exclusions:

- These measures are applicable to any small, large commercial and industrial pipe insulation retrofit (i.e., non-new construction) application. They cannot be used for residential purposes.
- Replacement of damaged or existing insulation is not eligible for a rebate.
- California Building Standards Code (Title 24), Section 123, establishes requirements for pipe insulation in the design and installation of space-conditioning and service water heating systems and equipment. Any pipe requiring insulation according to these standards does not qualify for a rebate. Details are available at energy.ca.gov/title24.
- Pipe insulation for exposed steam and hot-water pipes within 7 feet of the floor that are not otherwise guarded in order to prevent contact does not qualify for rebate. Occupational Safety and Health Administration (OSHA) standards require that exposed, heated surfaces be covered to prevent injury.

Additional details:

Project cost can include installation and material cost.

continued

Pipe diameter is less than or equal to 1 inch

Rebate Code	Description	Rebate/Unit Measure
PR051	1 inch insulation layer, ≤ 1 inch pipe, ≤ 15 psig steam, outdoor	\$3/linear ft.
PR052	1 inch insulation layer, ≤ 1 inch pipe, > 15 psig steam, outdoor	\$3/linear ft.
PR053	1 inch insulation layer, ≤ 1 inch pipe, hot water, outdoor	\$3/linear ft.
PR060	1 inch insulation layer, ≤ 1 inch pipe, ≤ 15 psig steam, indoor	\$3/linear ft.
PR061	1 inch insulation layer, ≤ 1 inch pipe, > 15 psig steam, indoor	\$3/linear ft.
PR062	1 inch insulation layer, ≤ 1 inch pipe, hot water, indoor	\$3/linear ft.
PR069	Fitting insulation ≤ 1 inch pipe, ≤ 15 psig steam, indoor	\$3/fitting
PR070	Fitting insulation ≤ 1 inch pipe, > 15 psig steam, indoor	\$3/fitting
PR071	Fitting insulation ≤ 1 inch pipe, hot water, indoor	\$3/fitting
PR078	Fitting insulation, ≤ 1 inch pipe, ≤ 15 psig steam, outdoor	\$3/fitting
PR079	Fitting insulation, ≤ 1 inch pipe, > 15 psig steam, outdoor	\$3/fitting
PR080	Fitting insulation, ≤ 1 inch pipe, hot water, outdoor	\$3/fitting

Pipe diameter larger than 1 inch and less than or equal to 4 inches

Rebate Code	Description	Rebate/Unit Measure
PR057	1 inch insulation layer, 1 inch < pipe ≤ 4 inch, 15 psig steam, outdoor	\$3/linear ft.
PR058	1 inch insulation layer, 1 inch < pipe ≤ 4 inch, > 15 psig steam, outdoor	\$3/linear ft.
PR059	1 inch insulation layer, 1 inch < pipe ≤ 4 inch, hot water, outdoor	\$3/linear ft.
PR066	1 inch insulation layer, 1 inch < pipe ≤ 4 inch, ≤ 15 psig steam, indoor	\$3/linear ft.
PR067	1 inch insulation layer, 1 inch < pipe ≤ 4 inch, > 15 psig steam, indoor	\$3/linear ft.
PR068	1 inch insulation layer, 1 inch < pipe ≤ 4 inch, hot water, indoor	\$3/linear ft.
PR075	Fitting insulation 1 inch < pipe ≤ 4 inch, ≤ 15 psig steam, indoor	\$3/fitting
PR076	Fitting insulation 1 inch < pipe ≤ 4 inch, > 15 psig steam, indoor	\$3/fitting
PR077	Fitting insulation 1 inch < pipe ≤ 4 inch, hot water, indoor	\$3/fitting
PR084	Fitting insulation, 1 inch < pipe ≤ 4 inch, ≤ 15 psig steam, outdoor	\$3/fitting
PR085	Fitting insulation, 1 inch < pipe ≤ 4 inch, > 15 psig steam, outdoor	\$3/fitting
PR086	Fitting insulation, 1 inch < pipe ≤ 4 inch, hot water, outdoor	\$3/fitting

Pipe diameter is greater than 4 inches

Rebate Code	Description	Rebate/Unit Measure
PR054	1 inch insulation layer, > 4 inch pipe, ≤ 15 psig steam, outdoor	\$3/linear ft.
PR055	1 inch insulation layer, > 4 inch pipe, > 15 psig steam, outdoor	\$3/linear ft.
PR056	1 inch insulation layer, > 4 inch pipe, hot water, outdoor	\$3/linear ft.
PR063	1 inch insulation layer, > 4 inch pipe, ≤ 15 psig steam, indoor	\$3/linear ft.
PR064	1 inch insulation layer, > 4 inch pipe, > 15 psig steam, indoor	\$3/linear ft.
PR065	1 inch insulation layer, > 4 inch pipe, hot water, indoor	\$3/linear ft.
PR072	Fitting insulation > 4 inch pipe, ≤ 15 psig steam, indoor	\$3/fitting
PR073	Fitting insulation > 4 inch pipe, > 15 psig steam, indoor	\$3/fitting
PR074	Fitting insulation > 4 inch pipe, hot water, indoor	\$3/fitting
PR081	Fitting insulation, > 4 inch pipe, ≤ 15 psig steam, outdoor	\$3/fitting
PR082	Fitting insulation, > 4 inch pipe, > 15 psig steam, outdoor	\$3/fitting
PR083	Fitting insulation, > 4 inch pipe, hot water, outdoor	\$3/fitting

Definitions

Air Conditioning, Heating and Refrigeration Institute (AHRI): This organization offers product information and testing procedures. For more information, visit ahrinet.org.

American Society of Heating, Refrigerating and Air-Conditioning Engineers (ASHRAE): This organization provides lists of program-qualifying products and information on test procedures. For more information, visit ashrae.org.

Annual Fuel Utilization Efficiency (AFUE): This measures the percentage of fuel that is converted into usable heating energy. For example, a 90 percent AFUE furnace means that 90 percent of the fuel is used in heating a facility, while 10 percent escapes as exhaust with the combustion gases.

Anti-Sweat Heaters (ASH): ASH are typically applied to low-temperature refrigerated display cases to prevent glass doors from fogging and cold surfaces from forming condensation. Commonly, ASH stay on at full load around the clock. Their contribution to the cooling load and electric power consumption of the refrigeration system can be significant.

Ballast: This is a lighting component that controls the electrical current drawn in from a power source.

Btu: British thermal unit, which refers to the amount of heat required to raise the temperature of 1 pound of water by 1 degree Fahrenheit.

Btuh: British thermal units per hour.

Bubble Diffusion: This is a laundry method of inserting ozone into water by continuously bubbling ozone directly into the drum of the clothes washer throughout the wash cycle.

California Energy Commission's Appliance Efficiency Database: energy.ca.gov/appliances.

CEC: This refers to the California Energy Commission.

Climate Zones (CZ): Climate zones are based on energy use, temperature, weather and other factors. They are basically a set of geographic areas that are grouped according to similar climatic characteristics.

CO₂ Sensor: This device measures the parts per million (PPM) of CO₂ in the air.

Color Rendering Index (CRI): This is a measure of a light source's ability to show object colors "realistically" or "naturally" compared to a familiar reference source, either incandescent light or daylight.

Conditioned Area/Space: This term refers to an area being heated or cooled by the heating, ventilation and air conditioning (HVAC) system.

Consortium for Energy Efficiency (CEE): To learn more about CEE's Tier specifications, visit cee1.org.

Database for Energy Efficient Resources (DEER): This database contains information on selected energy-efficient technologies and measures.

Display Case: This equipment is designed to store and display chilled and/or frozen foodstuffs.

Electrical Testing Laboratory (ETL): This organization marks products of compliance to applicable electrical, gas and other safety standards. For more information, visit etl.com.

Electronically Commutated Motors (ECM): ECMs are synchronous motors that are powered by a DC electric source using an integrated inverter/switching power supply, producing an AC electric signal, which drives the motor.

End-Use Customers: This term refers to customers who acquire energy for their own consumption.

Energy Factor (EF): EF measures a water heater's efficiency, based on recovery efficiency, standby losses and cycling losses. The higher the EF, the more efficient the water heater. This measure is only used for residential-grade water heaters.

ENERGY STAR®: To learn more about ENERGY STAR's energy-efficiency specifications, visit energystar.gov/cfs.

Fixture: Generally, a light fixture is an electrical device used to create artificial light by use of an electric lamp. All light fixtures have a fixture body and a socket to hold the lamp and allow for its replacement. For PG&E lighting rebates, a fixture refers to new equipment being installed based on system wattage (lamp and ballast for fluorescent fixtures).

HID: This refers to high-intensity discharge.

High-Performance Linear Fluorescent Fixture Ballasts: This term refers to National Electrical Manufacturers Association (NEMA) premium or Consortium for Energy Efficiency (CEE)-qualified T8 ballasts or T5 ballasts.

High-Performance Linear Fluorescent Lamps: This refers to Consortium for Energy Efficiency (CEE)-qualified 4-foot T8 lamps or 2-foot T8/T5 lamps with at least 20,000-hour-rated life and a Color Rendering Index (CRI) that meets or exceeds 82.

Horsepower (hp): This is a unit of power equal to 550 foot-pounds per second.

Ice Making Head (IMH): Automatic commercial ice makers that do not contain integral storage bins, but are generally designed to accommodate a variety of bin capacities. Storage bins entail additional energy use not included in the reported energy consumption figures for these units.

Indoor Tank: This refers to a tank located in an enclosed indoor space, where it is not exposed to sun or wind.

Integrated Retrofit Kits: These replace existing fluorescent lamps, sockets and ballasts, along with the lens and frame, and they can be installed easily into the existing fluorescent fixture. Troffers provide the required electrical components, LED light sources and optical elements, which include new lens and door frame—all in a prepackaged kit.

K-Value: This refers to thermal conductivity and has a unit of Btu-inch per hour, per square foot, per degree Fahrenheit.

Kilolumen: A kilolumen is 1,000 lumens.

Large Office: This refers to office buildings typically greater than 20,000 square feet.

Large Retail: Retail buildings that are typically greater than 5,000 square feet.

Light-Emitting Diode (LED): LED is a light-emitting diode product that is assembled into a lamp (or light bulb) for use in lighting fixtures. LED lamps have a lifespan and electrical efficiency that is several times better than incandescent lamps, and significantly better than most fluorescent lamps, with some chips able to emit more than 100 lumens per watt.

Low Temperature: For freezers, refrigerated space temperatures are considered “low” if they are below 32 degrees Fahrenheit.

Lumen (lm): A lumen is the unit of light output.

MBtu: 1,000 British thermal units.

MBtuh: 1,000 British thermal units per hour.

Medium Temperature: For coolers, refrigerated space temperatures are considered “medium” if they are between 32 to 50 degrees Fahrenheit.

Minimum Energy Efficiency Ratio (EER): EER is a measure of the efficiency of the unit. It indicates the cooling capacity in Btu per watt hour. The higher the EER rating, the higher the efficiency of the unit.

National Electrical Manufacturers Association (NEMA) Premium Ballasts: These are the most efficient fluorescent fixed output and dimmable electronics for T8 ballasts to be recognized by NEMA.

NEMA Premium Motor: This is an alternating current (AC) induction motor that has a certified efficiency rating from NEMA.

Parking Garage: A parking garage is a covered building or structure for the purpose of parking vehicles, which consists of at least a roof over the parking area, enclosed with walls on all sides. Parking garages may have fences, rails, partial walls (pony wall) or other barriers in place of one or more walls. The structure has an entrance(s) and exit(s) and includes areas for vehicle maneuvering to reach the parking spaces. If the roof of the parking structure is also used for parking, the section without an overhead roof is considered a parking lot instead of a parking garage.

Permanent Mag Motor: This term refers to a permanent magnet alternating current (AC) motor.

Pounds per Square Inch (PSIG): This refers to the pounds of steam pressure per square inch, as shown on a gauge. The steam system should have a steam pressure gauge attached that reads the pressure of the steam in the pipes. The pressure gauge will register in pounds of pressure per square inch.

Reach-in Cabinets: These are refrigerated retail display cabinets with chilled glass door(s) and horizontal/semi-horizontal merchandising. Cabinets enable customers to view contents even when closed, and enable customers to self-serve. Styles include:

- “Plug-in” refrigerated display cabinets with integral refrigeration systems (for example, incorporating a compressor and condensing unit)
- “Remote” refrigerated display cabinets designed to work with a nonintegral refrigeration system (for example, where the compressor and condenser, or all or parts of the refrigeration system, are located at a different location from the cabinet)

Remote Condensing Unit (RCU): A type of automatic commercial ice maker in which the ice-making mechanism and condenser or condensing unit are in separate sections. This includes ice makers with and without remote compressor.

R-Value: Insulation is rated in terms of thermal resistance, called R-value, which indicates the resistance to heat flow. A greater R-value corresponds with a greater insulating effectiveness.

Self-Contained Unit (SCU): A type of automatic commercial ice maker in which the ice-making mechanism and storage compartment are in an integral cabinet.

Shaded-Pole Motor: This type of motor is the original form of an AC single-phase induction motor.

Small Office: This refers to office buildings that are typically less than 20,000 square feet.

Small Retail: This refers to retail buildings that are typically less than 5,000 square feet.

System Types: Commercial refrigeration equipment can be classified into two categories: split-system refrigeration systems and self-contained refrigeration systems. Split-system configurations have a condenser unit that is located remotely, usually on the rooftop, which allows it to exchange heat with the outside air. Self-contained units have all of the components, including the condenser, contained in a single package.

Thermal Efficiency (TE): Measures a water heater’s efficiency, based on recovery efficiency, standby losses and cycling losses. The higher the TE, the more efficient the water heater. It is only used for nonresidential grade water heaters.

Ton: When used in reference to air conditioning systems, a ton is the unit of measurement that is the cooling capacity of the system and is 12,000 Btuh.

Total Washer Capacity: This refers to the rated capacity of installed and operating washing machine units that will be connected to an ozone laundry system. This is normally measured in pounds capacity.

Troffer: A troffer is a rectangular light fixture that fits into a modular dropped ceiling grid.

Underwriters Laboratories (UL): This independent product safety certification organization’s website is ul.com.

Uniform Energy Factor (UEF): This measures a water heater's efficiency, based on recovery efficiency, standby losses and cycling losses. The higher the UEF, the more efficient the water heater. UEF is used to measure both residential and nonresidential water heaters.

Variable Frequency Drive (VFD): This electric motor control changes the driven motor's input power frequency measured in cycles per second by either manual setting or variable input from one or more sensors.

Venturi Injection: This laundry method inserts ozone, using very high pressure, directly into the cold-water supply line leading to a washer.

Walk-in Coolers/Freezers: Also known as "walk-ins," these are insulated refrigerated spaces with access doors large enough for people to enter. Walk-ins are used for food storage and merchandising in the food service and food sales applications.

More ways for your business to save money

To find the latest rebate information and catalogs or to apply for rebates online, visit [pge.com/businessrebates](https://www.pge.com/businessrebates).

PG&E offers a wide range of tools and resources that can help your business save energy and money while helping the environment.

- Check out PG&E's Calculated Incentives for businesses if you did not find a rebate matching the high-efficiency equipment you would like to install. To learn more, visit [pge.com/cr](https://www.pge.com/cr).
- Sign up for automated benchmarking service at [pge.com/benchmarking](https://www.pge.com/benchmarking), which allows you to use the ENERGY STAR® Portfolio Manager to track and compare your facility's energy performance over time.
- Use PG&E's audit tools to identify options for saving energy and money at your facility, and get started on developing a comprehensive energy management plan. Visit the Business Energy Checkup at [pge.com/waystosave](https://www.pge.com/waystosave).
- Find out how you can earn incentives for large custom projects, including equipment upgrades and retrocommissioning, by using PG&E's Calculated Incentives Program. Visit [pge.com/customized](https://www.pge.com/customized) and [pge.com/rcx](https://www.pge.com/rcx).
- Explore PG&E's demand response programs, which offer incentives for managing your energy use during times of peak demand. Visit [pge.com/demandresponse](https://www.pge.com/demandresponse).
- Check out PG&E's third-party programs at [pge.com/thirdparty](https://www.pge.com/thirdparty). These programs are managed by energy-efficiency specialists and offer a range of services to provide you with industry-specific, energy-saving solutions—from dairies and wineries to food processors.
- Use PG&E's Savings By Design or Customized New Construction programs to build in energy efficiency from the ground up and earn incentives at the same time. To get started, visit [pge.com/savingsbydesign](https://www.pge.com/savingsbydesign).
- Go to the Agriculture and Food Processing section of PG&E's website at [pge.com/ag](https://www.pge.com/ag) to learn about loans and grants that focus on food, agribusiness, alternative energy and environmental programs, or call our **Agricultural Customer Service Center** at [1-877-311-FARM \(3276\)](tel:1-877-311-FARM).
- If you are considering generating your own electricity, talk to your PG&E account representative about incentives for solar, wind and fuel cell self-generation equipment.

You also may learn more about these programs, tools and offers by contacting your local PG&E account representative or by calling our **Business Customer Service Center** at [1-800-468-4743](tel:1-800-468-4743).

Ready to get started with your next project and need the help of a contractor? Find local vendors who participate in PG&E's energy-efficiency rebate programs for your business at [pge.com/tradeprodirectory](https://www.pge.com/tradeprodirectory).